



Typ			DAP 450-80	DAP 850-80	DAP 1300-80	DAP 1700-80	DAP 2100-80	DAP 2800-80	DAP 3400-80
Capacity		kN	4.5	8.5	13	17	21	28	34
Return force		kN	4	4	4	4	20	27	33
Working stroke		mm	80	80	80	80	80	80	80
Ram plate area	F	mm	315 x 315	315 x 315	315 x 315	315 x 315	315 x 315	315 x 315	315 x 315
Maximum daylight	B	mm	387	387	387	387	387	387	387
Working surface	F x G	mm	360 x 175	360 x 175	360 x 175	360 x 175	360 x 175	360 x 175	360 x 175
Slot width similar to DIN 650		mm	14	14	14	14	14	14	14
Air connection			G3/8"	G3/8"	G3/8"	G3/8"	G3/8"	G3/8"	G3/8"
Air consumption per 10 mm stroke		l	1.0	1.5	2.1	2.6	3.0	3.7	4.5
Space required	C x G	mm	500 x 315	500 x 315	500 x 315	500 x 315	500 x 315	500 x 315	500 x 315
Frame height	K	mm	590	590	590	590	590	590	590
Cylinder height	M	mm	443	569	695	821	741	889	1037
Weight		kg	197	200	203	206	212	219	226